

EYE CONTACT:

Move victim away from exposure to vapors and into fresh air. If irritation or redness develops, seek medical attention. For direct contact, hold eyelids apart and flush the affected eye(s) with clean water for at least 15 minutes. Seek medical attention.

SKIN CONTACT:

Remove contaminated clothing. Cleanse affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and persists, seek medical attention.

INHALATION (BREATHING):

If respiratory symptoms or other symptoms of exposure develop, move victim away from source of exposure and into fresh air. If respiratory symptoms or other symptoms of exposure develop, seek medical attention. If victim is not breathing, artificial respiration should be administered. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek medical attention.

INGESTION (SWALLOWING):

Aspiration Hazard - **DO NOT INDUCE VOMITING** or give anything by mouth because this material can enter the lungs and cause severe lung damage. If victim is drowsy or unconscious, place on the left side with head down. If possible, do not leave victim unattended. Seek medical attention.

*** Note to physician:**

Epinephrine and other sympathomimetic drugs may potentiate cardiac arrhythmias in persons exposed to this chemical. These drugs should be administered cautiously, if at all, and only with cardiac monitoring.

SECTION VI - REACTIVITY DATA

STABILITY: UNSTABLE X STABLE

HAZARDOUS POLYMERIZATION: MAY OCCUR X WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS:

Combustion may yield carbon monoxide and/or carbon dioxide.

CONDITIONS TO AVOID:

Keep product away from heat, sparks, pilot lights, static electricity, and open flame.

INCOMPATIBILITY (MATERIALS TO AVOID):

This product is incompatible with strong acids or bases, oxidizing agents and selected amines.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Shut off and eliminate all ignition sources. Keep people away. Recover free product. Add sand, earth or other suitable absorbent to spill area. Minimize breathing vapors. Minimize skin contact. Ventilate confined spaces. Open all windows and doors. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses, or extensive land areas. Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, flammable vapors from absorbed material.

WASTE DISPOSAL METHOD:

Dispose of in accordance with local, state and federal regulations.

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION:

Avoid prolonged or repeated breathing of vapors. If exposure may or does exceed occupational exposure limits use a NIOSH approved respirator to prevent overexposure.

VENTILATION:

If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits (see Section II), additional ventilation or exhaust systems may be required. Where explosive mixtures may be present, systems safe for such locations should be used.

PROTECTIVE GLOVES:

The use of gloves impermeable to the specific material handled is advised to prevent skin contact, possible irritation and absorption.

EYE PROTECTION:

Approved eye protection to safeguard against potential eye contact, irritation or injury is recommended.

OTHER PROTECTIVE EQUIPMENT:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

HYGIENIC PRACTICES:

Wash with soap and water.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Keep containers tightly closed. Keep containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. Avoid inhalation of vapors and personal contact with the product. Use good personal hygiene practice. "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition; they may explode and cause injury or death. "Empty" containers should be completely drained, properly bunged and promptly shipped to the supplier or a drum reconditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

SECTION X - REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.
TSCA STATUS:

All chemicals found in this product comply with the Toxic Substance Control Act inventory reporting requirements.

EPA SARA TITLE III CHEMICAL LISTINGS:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME:	CAS NUMBER:	CONCENTRATION:
Hexane	110-54-3	80.79
Polyisoprene	9003-31-0	10%-15%
Rosin Ester	85026-55-7	1%-4%
Zinc Oxide	8051-03-4	1%-3%
Petroleum Oil	8042-47-5	1%-3%
Lanolin	8044-50-6	0.5%-2%

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS PRODUCT OR INFORMATION, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. The information and product are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use thereof.